

Appl. No. 10/827,088  
Docket No. 9606  
RCE / Amendment dated January 17, 2008  
Reply to Final Action mailed on October 4, 2007  
Customer No. 27752

RECEIVED  
CENTRAL FAX CENTER  
JAN 17 2008

### AMENDMENTS TO THE CLAIMS

#### Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A disposable absorbent article comprising:
  - a) a liquid pervious topsheet;
  - b) a liquid impervious backsheet that is at least partially joined to the topsheet;
  - c) an absorbent core disposed at least partially between the topsheet and the backsheet; and
  - d) a wetness indicator printed onto a surface of said backsheet; the wetness indicator comprising a graphic that further comprises at least one hydrolyzable color composition and a varnish coating disposed adjacent to said hydrolyzable color composition;wherein upon wetting, said hydrolyzable color composition undergoes a chemical hydrolytic reaction whereupon resulting in said graphic becomes visible to the unaided eye.
2. (Original) The article of claim 1 wherein the color composition comprises:
  - a) from about 1% to about 10%, by weight of the composition, of fluid dyestuffs; and
  - b) from about 10% to about 99%, by weight of the composition, of a solvent.
3. (Original) The article of claim 2 wherein the solvent is a non-aqueous solvent selected from the group consisting of alcohols, acetates, and combinations thereof.

Appl. No. 10/827,088

Docket No. 9606

RCE / Amendment dated January 17, 2008

Reply to Final Action mailed on October 4, 2007

Customer No. 27752

4. (Original) The article of claim 3 wherein said alcohol is selected from the group consisting of isopropyl alcohol, n-propyl alcohol, ethanol, methanol, and combinations thereof.
5. (Original) The article of claim 3 wherein said acetate is selected from the group consisting of isopryl acetate, n-propyl acetate, and combinations thereof.
6. (Original) The article of claim 1 wherein said varnish coating comprises materials selected from the group consisting of acrylic copolymers, shellac-based acrylic resins, polyamides, and combinations thereof.
7. (Original) The article of claim 1 wherein said wetness indicator is printed on an inner surface.
8. (Previously presented) The article of claim 1 wherein said varnish coating is disposed over said hydrolyzable\_color composition.
9. (Previously presented) The article of claim 1 wherein said varnish coating is disposed beneath said hydrolyzable color composition.
10. (Previously presented) The article of claim 8 wherein said varnish coating is further disposed beneath said hydrolyzable color composition.
11. (Currently amended) A method of printing a wetness indicator onto an absorbent article:

Appl. No. 10/827,088  
Docket No. 9606  
RCE / Amendment dated January 17, 2008  
Reply to Final Action mailed on October 4, 2007  
Customer No. 27752

- a) providing an absorbent article wherein said article comprises a topsheet, a backsheet and an absorbent core;
- b) disposing between said backsheet and said absorbent core via printing a wetness indicator onto a surface of said backsheet; the wetness indicator comprising a graphic that further comprises at least one hydrolyzable color composition and a varnish coating disposed adjacent to said hydrolyzable color composition;

wherein upon wetting, said hydrolyzable color composition undergoes a ~~chemical~~ hydrolytic reaction whereupon resulting in said graphic becomes visible to the unaided eye.

12. (Previously presented) The article of claim 1 wherein the backsheet is either breathable or non-breathable.

13. (Previously presented) The article of claim 2 wherein the fluid dyestuff is selected from the group consisting of D&C Red 27, D&C Orange 5 and combinations thereof.

14. (Currently amended) A disposable absorbent article comprising:

- a) a liquid pervious topsheet;
- b) a liquid impervious backsheet that is at least partially joined to the topsheet;
- c) an absorbent core disposed at least partially between the topsheet and the backsheet; and
- d) a wetness indicator printed onto a surface of said backsheet; the wetness indicator comprising a graphic that further comprises at least one hydrolyzable color composition; a first varnish coating disposed over said hydrolyzable color composition; and a second varnish coating disposed beneath said hydrolyzable color composition;

Appl. No. 10/827,088

Docket No. 9606

RCE / Amendment dated January 17, 2008

Reply to Final Action mailed on October 4, 2007

Customer No. 27752

wherein upon wetting, said hydrolyzable color composition undergoes a hydrolytic reaction forming a carboxylic acid, and resulting in said graphic becoming visible to the unaided eye.

15. (Previously presented) The article of claim 14 wherein the backsheet is either breathable or non-breathable.

16. (Previously presented) The article of claim 1 wherein said chemical reaction forms a carboxylic acid.